#### You want to learn more about us?

Feel free to ask for a meeting on our premises. Detailed information on the company and on our product range is also available on-line at www.huerner.de





# HÜRNER WhiteLine Manual Hydraulic

# HÜRNER

SCHWEISSTECHNIK

#### HÜRNER Schweisstechnik GmbH

Nieder-Ohmener Str. 26 35325 Mücke GERMANY

Ph +49 6401 9127 0 Fx +49 6401 9127 39 E-Mail info@huerner.de Internet: www.huerner.de

# HÜRNER Welding Technology NZ Ltd

12 Croskery Road Papakura Auckland 2110 NEW ZEALAND Ph +64 9 299 3640

NEW ZEALAND

Ph +64 9 299 3640

Fx +64 9 299 3740

E-Mail r.gruen@xtra.co.nz

Internet: www.huerner.co.nz

## HÜRNER Schweisstechnik Gulf L.L.C

Damascus Street, Al Qusais 4 DUBAI P.O.Box 233586 UNITED ARAB EMIRATES Ph +971 4 2584886

Ph +971 4 2584886 Fx +971 4 2584887 E-Mail info@hurnergulf.ae Internet: www.huerner.de Manual 2.0 800-1000-1



# Manual Hydraulic

The Manual Hydraulic Series of butt-welding machines in the new WhiteLine generation makes a statement by its superior manufacturing quality and its scalability in the form of an easy upgrade to a data logging-enabled machine with the installation of an SPG 2.0 data logger for welding report generation.

- The machine ships with a hydraulic unit that features, as a unique first, a totally integrated enclosure that also is a splash and dirt shield for all components on the inside. The front panel controls, too, are included in the ingress protection according to the IP 54 rating (where IP 64 is possible upon request).
- All connections, including an additional power socket free to use for the operator's convenience, are located at the back of the controller. Both the facing tool and the heating element are also connected at the back panel of the hydraulic controller. Therefore, no additional power distribution unit is needed.
- The hydraulic unit also doubles as the central control panel of the machine with

which the user performs all relevant settings and process steps. The front panel features a GT keypad, the critical process controls, and also the digital temperature control for the heating element and the extra-large and conveniently readable pressure gauge.

- All **HÜRNER** Manual Hydraulic butt-welding machines can easily be upgraded with the HÜRNER data logger SPG 2.0 for welding parameter viewing, monitoring, and recording. As a consequence the model version "Manual + SPG" of the butt-welding machine complies with mains gas distributors' specification requirements, which state that data recording and report generation is mandatory, but do not require automatic welding processes.
- The machine chassis is set on a specifically developed support frame exhibiting a warp resistance that manages with ease even the most extreme pipe parameters. Operators can be sure that the machine chassis does not tilt or twist even when very long lengths of pipe with very thick walls are processed.

- Large, knurled turning knobs mean easy handling for the operator who opens or closes the clamps of the machines sized up to O.D. 315. No tools are needed for this.
- The facing tool with integrated micro-safety switch is driven by a high-quality power drive engaged by a transmission chain. The precision heating element ships with a very rugged anti-stick coating.
- A carrying rack is provided for the heating element and the facing tool, to store them with no worries about the heat.
- Maximum protection of the machine, while it is stowed away, is provided (up to O.D. 315) by an optionally available, high-quality transport box that has been specifically designed for the entire machine assembly, with drawer-style storage compartments for the reducer inserts.
- For all machines a welding neck support is of course available, too.

# All components are covered by the HÜRNER warranty.



200-704-100

630 - 1000

400 V

50 Hz. 3 P

21.2

1135

630 - 1200

400 V 50 Hz, 3 P

23.0

1998

630, 710,

800, 900,

1000

Centralized temperature control



All connections at the back panel of the hydraulic unit



Transport box



Welding neck support

### HÜRNER Manual Hydraulic characteristics

Howell Mariaar Hydraalic Characteristics	
Welding monitoring system	Heating element temperature
Display screen	Numeric 7-segment characters, character height 10 mm
Approvals, quality, ingress protection	CE, ISO 9001: 2015, IP 54 (IP 64 optional), WEEE Reg. No. DE 74849106, RoHS-compliant
Hydraulic unit	Only one external power supply needed, all connections and a power socket for the operator's convenience at the back of the enclosure <sup>1)</sup> Digital heating element temperature control, adjustable at the hydraulic unit Hydraulic unit fully encased in rugged steel enclosure weighing as little as 19.5 kg (up to O.D. 335 mm) Max. pressure, up to O.D. 355 mm, 130 bar, O.D. 500 - 630 mm, 150 bar, O.D. 800 - 1600 mm, 220 bar Accurate and maintenance-free gauge showing the welding pressures  Easy upgrade of the hydraulic and control unit with a SPG 2.0 data logger for report generation  Pressure sensor 160 bar installable to the hydraulic unit  Specifically designed support for construction site-suitable installation of the data logger to the edge of the hydraulics  Pressure and temperature lines connected directly to the hydraulic unit with very short lengths of hose or cable  Power supply to the data logger from the power socket of the hydraulic unit

Manufacturer warranty 1) Only if prepared for SPG data logge

HÜRNER WhiteLine

Manual Hydraulic

Stand-alone in Butt-Welding

160 mm

200-721-16

40 - 160

230 V

50 Hz

2.45

66

40, 50, 63, 75, 90, 110, 125, 140

П

250 mm

200-704-25

(63) 75 - 250

230 V 50 Hz

3.65

109

(63)\*<sup>)</sup>, 75, 90, 110, 125, 140,

63 - 200

230 V

50 Hz

3.45

87

63, 75, 90, 110, 125, 140,

315 mm

90 - 315

230 V

50 Hz

4.65

168

90, 110, 125, 140, 160, 180,

200, 225 250, 280

90 - 355

230 V 50 Hz

5.25

201

90, 110, 125,

140, 160, 180, 200,

200 - 500

400 V

50 Hz. 3 P

6.45

295

200, 225, 250, 280, 315, 355,

315 - 630

400 V

50 Hz. 3 P

11.65

448

315 , 355, 400, 450.

500, 560

500 - 800

400 V 50 Hz, 3 P

16.8

771

Technical Specs

Welding range O.D. (mm)

**Power Supply** 

Rated power (kW)

Overall weight with all components (kg)

Reducer inserts

Welding neck support\*)

Automatic, "jumping" heating element\*) Included standard de Hydraulic controller

for Manual with centralized controls Basic machine chassis Facing tool with

PTFE-coated heating element

HÜRNER transport box for reduc-

ers and machine, HÜRNER aluminium reducers1 HÜRNER steel reducers1

Carrying rack

\*) Available as an option

<sup>2)</sup> Under development

<sup>1)</sup> Modified design: Screw-Fastened